

EZ BREAK

Drying Agent

DESCRIPTION

An ultra-concentrated sheeting drying agent that sheds water in large sheets to reduce the effects of "small sticky droplet syndrome." This drying agent works best in tunnels where space is available between application and the blowers.

USAGE INSTRUCTIONS

This product is ideally applied under low pressure application in tunnel and in-bay automatic settings. Begin application at 850-1250:1. For high pressure application apply at 1500-2500:1. In applications where greater amounts of rinse water are applied to the vehicle stronger dilutions of product may be required.

FEATURES

- Ultra-concentration reduces cost
- Reduction of "small sticky droplet syndrome"
- New drying agent technology
- Pleasant berry fragrance

SIZES AVAILABLE

5-gallon pails Code: 10-50114-005
15-gallon drums Code: 10-50114-015
30-gallon drums Code: 10-50114-030
55-gallon drums Code: 10-50114-055

SPECIFICATIONS

COLOR: Purple
FRAGRANCE: BERRY
FOAM: White
PH: 8

Drop Count (Titration)	Oz/Gal of water	Ratio to 1
3	0.03	4266
4	0.04	3199
5	0.05	2559
6	0.06	2132
7	0.07	1828
8	0.08	1599
9	0.09	1421
10	0.10	1279
11	0.11	1163
12	0.12	1066
13	0.13	984
14	0.14	913



**ANYTHING
BUT ORDINARY**