DESCRIPTION

Lower your drying agent costs by using this product. This highly concentrated drying agent is designed to bead water to promote more effective drying. This drying agent is a no frills product that will deliver results time after time.

USAGE INSTRUCTIONS

This product is ideally applied under low pressure application in tunnel and in-bay automatic settings. Begin application at 1000-1500:1. For high pressure application apply at 1700-2500:1. In applications where greater amounts of rinse water are applied to the vehicle stronger dilutions of product may be required.

FEATURES

- Rapidly beads water
- Consistently works in all applications
- Biodegradable
- Highly concentrated for minimal usage

SPECIFICATIONS

COLOR:	BLUE
FRAGRANCE:	NONE
FOAM:	NA
PH:	8-9

SIZES AVAILABLE

5-gallon pails	Code:	11-77600-005
15-gallon drums	Code:	11-77600-015
30-gallon drums	Code:	11-77600-030
55-gallon drums	Code:	11-77600-055

Drop Count	Oz/Gal of	
(Titration)	water	Ratio to 1
1	0.02	7679
2	0.03	3839
3	0.05	2559
4	0.07	1919
5	0.08	1535
6	0.10	1279
7	0.12	1096
8	0.13	959
9	0.15	852
10	0.17	767
11	0.18	697
12	0.20	639

